

## Single-arm YuMi®

The latest member of the YuMi family



Single-arm YuMi is ABB's most agile and compact collaborative robot yet, and can be easily integrated into any production environment.

Following on from the success of ABB's dual-arm YuMi, introduced in 2015, the world's first truly collaborative robot, ABB has developed a single-arm YuMi to expand its collaborative portfolio.

### Versatile installation for convenient deployment

Single-arm YuMi is compact and lightweight (9.5 kg) and supports mounting in any direction including ceiling, table, and wall mounting for rapid and flexible installation to fit into existing production lines. The ultra-light magnesium arm rotates on seven axes to mimic human-like movements with greater agility than 6-axis robots. The robot was specifically designed to meet the flexible production needs required by small parts assembly processes including consumer electronics, consumer goods, and small and medium enterprises.

### Easy-to-use lead-through programming

Single-arm YuMi also features the same intuitive, easy-to-use lead through programming as dual-arm YuMi, meaning workers can teach the robot motions and positions easily and quickly, greatly simplifying robot programming. Combining this simplicity with the robot's deployment flexibility, it will help manufacturers in many industries to offset shortages of skilled workers and help reduce entry barriers for new potential robot users, particularly small and medium enterprises.

Extremely versatile, the YuMi family of robots can be combined in numerous configurations. For example, a single-arm YuMi can be used to feed parts to dual-arm YuMi to increase flexibility, or added as an extra arm for more complex assembly tasks requiring more than 2 robot arms.

### SaveMove2 option

To fulfill the enhanced safety requirements of specific usage scenarios, ABB's SafeMove 2 will be available as option for the single-arm YuMi, giving it the full range of safety certified functions that other ABB robots have.

### Key features

- 500g rated payload
- Small footprint, 7-axis dexterity
- Very lightweight manipulator, 9.5 kg
- Mounting in any position
- Integrated Gripper with vision and vacuum
- Best-in-class safety design
- High speed and accuracy
- PL d Cat 3 Protective stop and emergency stop

### Customer benefits

- Short cycle times
- Fenceless operation
- Easy programming with lead-through
- Lower investment
- Easier to integrate

## Specification

Robot version	Reach (mm)	Payload (g)	Armload
IRB 14050	559	500	No armloads
<b>Features</b>			
Integrated signal and power supply	24V Ethernet or 4 Signals		
Integrated air supply	4 Bar		
Integrated ethernet	One 100/10 Base-TX ethernet port		
Position repeatability	0.02 mm		
Robot mounting	All angles, including table mounting, wall mounting, and ceiling mounting		
Degree of protection	IP30		
Functional safety	PL d Cat 3 Protective stop and emergency stop PL b Cat b Speed supervision SafeMove 2 Pro as option		
Controller	OmniCore		

## Performance

IRB 14050	
0.5 kg picking cycle	
25* 300 * 25 mm	0.86s
Max TCP Velocity	1.5 m/s
Max TCP Acceleration	11 m/s*s
Acceleration time 0-1m/s	0.12s


## Technical information

Physical	
Dimensions bottom	160 mm x 160 mm
Weight	9.5 kg


## Movement

Axis movement	Working range	Maximum speed
Axis 1 rotation	-168.5° to 168.5°	180°/s
Axis 2 arm	-143.5° to 43.5°	180°/s
Axis 3 arm	-123.5° to 80.0°	180°/s
Axis 4 wrist	-290.0° to 290.0°	400°/s
Axis 5 bend	-88.0° to 138.0°	400°/s
Axis 6 turn	-229.0° to 229.0°	400°/s
Axis 7 rotation	-168.5° to 168.5°	180°/s


## Front view



## Top view



## Side view



## Isometric view

